

2001 Ram
Engine

Component	Fluids, Lubricants and Genuine Parts
Engine Coolant	Mopar Antifreeze/Coolant 5 Year/100,000 Mile Formula HOAT (Hybrid Organic Additive Technology) P/N 5011764AB or equivalent. Engine Oil for the proper quality and SAE Grade oil for your engine, refer to the section Maintenance Procedures.
3.7/5.2L Engine Oil	Use SAE 5W-30, API Certified, meeting material standard MS-6395.
5.9L Engine Oil	Use SAE 5W-20, API Certified, meeting material standard MS-6395.
Engine Oil Filter	Mopar Engine Oil Filter, P/N 05083285AA or equivalent.
Fuel Selection (all except 5.9L)	87 Octane
Fuel Selection (5.9L)	89 Octane (87 Octane acceptable)

Chassis

Component	Fluids, Lubricants and Genuine Parts
Automatic Transmission	Mopar ATF+4, Automatic Transmission Fluid
Transfer Case	Mopar ATF+4, Automatic Transmission Fluid
NVG 246 Automatic Transfer Case Only	Mopar PN 05179014AA, NVG 246 Automatic Transmission Fluid or equivalent.
Manual Transmission Fluid (G238)	Mopar Manual Transmission Fluid
Clutch Linkage	Multipurpose Grease, NLGI Grade 2 E.P. or equivalent.
1500 Model Front Axle (4x4)	GL-5 SAE 75W-90 or equivalent.
1500 Model Rear Axle	Mopar Synthetic Gear Lubricant SAE 75W-140 (MS-8985). Limited-Slip Rear Axle on 1500 Models require the addition of 118 ml (4 oz.) Mopar limited slip additive or equivalent.
2500/3500 Model Front and Rear Axle	Mopar Synthetic, GL-5 SAE, 75W-90 or equivalent. Limited-Slip 10.5/11.5 inch Rear Axles DO NOT REQUIRE a limited slip additive.
Brake Master Cylinder	Mopar DOT 3 and SAE J1703 should be used or equivalent. If DOT 3 brake fluid is not available, then DOT 4 is acceptable. Use only recommended brake fluids.
Power Steering Reservoir	Mopar Power Steering Fluid