

2001 Wrangler  
Engine

Engine Coolant	Mopar Antifreeze/Coolant 5 Year/100,000 Mile Formula HOAT (Hybrid Organic Additive Technology)
Engine Oil	Use SAE 5W-30, API Certified, meeting material standard MS-6395.
Oil Filter (2.4L Engine)	Mopar Oil Filter P/N 4105409
Oil Filter (4.0L Engine)	Mopar Oil Filter P/N 05281090
Fuel Selection	87 Octane

Chassis

Component	Fluids, Lubricants and Genuine Parts
Automatic Transmission	Mopar ATF+4, Automatic Transmission Fluid
Manual Transmission	Mopar Manual Transmission Fluid
Transfer Case	Mopar ATF+4, Automatic Transmission Fluid
Axle Differential (front-rear)	Mopar Hypoid Gear Lubricant (SAE 80W-90) (API GL5) or equivalent. For trailer towing, use a SAE 75W-140 Synthetic Gear Lubricant. Models equipped with Trac-Lok require an additive.
Brake Master Cylinder	Mopar DOT 3 and SAE J1703 should be used or equivalent. If DOT 3 brake fluid is not available, then DOT 4 is acceptable. Use only recommended brake fluids.
Power Steering Reservoir	Mopar Power Steering Fluid
Steering Gear & Linkage, Ball Joints, Prop Shafts & Yokes, Wheel Bearings	Mopar Multipurpose Lubricant NLGI Grade 2 EP, GC-LB