KJ

| Component   | Fluids, Lubricants and Genuine Parts                  |
|---|---|
| Automatic Transmission                            | Mopar ATF+4, Type 9602                                |
| Manual Transmission                               | Mopar Manual Transmission Fluid P/N 4874464           |
| Axle Differential (front-rear)                    | Mopar Gear Lubricant or equivalent of SAE 80W-90      |
|   | (API-GL5). For trailer towing applications use a SAE  |
|   | 75W-140 Synthetic Gear Lubricant in rear axle. Models |
|   | equipped with Quadra Drive System require SAE 75W-    |
|   | 140 Synthetic Gear Lubricant and Mopar Hypoid Gear    |
|   | Oil Additive Friction Modifier                        |
| Brake Master Cylinder & Anti-Lock Brake System    | Mopar Brake/Clutch Fluid or equivalent marked         |
| Reservoir   | FMVSS No. 116, DOT 3 and SAE J1703. CAUTION!          |
|   | Use only recommended brake fluids.                    |
| Hydraulic Clutch Reservoir                        | Use only Mopar Brake /Clutch Fluid or equivalent      |
|   | meeting standard FMVSS 116 and DOT-3.                 |
| Power Steering Pump                               | Mopar Power Steering Fluid                            |
| Transfer Case                                     | Mopar ATF+4, Type 9602 Automatic Transmission         |
|   | Fluid.  |
| Windshield Washer Fluid                           | Mopar Windshield Washer Solvent.                      |
| Ball Joints, Prop Shafts, U-Joints, Yokes & Wheel | Mopar Multi-purpose Lubricant or equivalent (labeled  |
| Bearings  | NLGI Grade 2 EP, GC-LB)                               |