

## Chassis

| Component   | Fluid, Lubricant, or Genuine Part   |
|---|---|
| Automatic Transmission                                      | Mopar® ATF+4 Automatic Transmission Fluid   |
| Transfer Case   | Selec-Trac Models - Mopar® ATF+4 Automatic Transmission Fluid. Quadra-Trac Models - Mopar® Transfer Case Fluid (P/N 05016796)   |
| Axle Differential (front-rear)                              | Mopar® Synthetic Gear Lubricant or equivalent of SAE 75W-140 (API-GL5) if equipped with a Vari-Lok® front axle. Mopar® Gear Lubricant or equivalent of SAE 80W-90 (API-GL5) if not equipped with a Vari-Lok® front axle. Mopar® Synthetic Gear Lubricant or equivalent of SAE 75W-140 (API-GL5) if equipped with a Dana M35 or M44 Vari-Lok® rear axle. Mopar® Gear Lubricant or equivalent of SAE 80W-90 (API-GL5) if equipped with a Dana M44 rear axle without Vari-Lok®. For trailer towing applications, use a SAE 75W-140 Synthetic Gear Lubricant in rear axle. Vari-Lok® equipped axles require a friction modifier additive. |
| Brake Master Cylinder                                       | Mopar® DOT 3, SAE J1703 should be used. If DOT 3, SAE J1703 brake fluid is not available, then DOT 4 is acceptable. Use only recommended brake fluids.  |
| Power Steering Reservoir                                    | Mopar® Power Steering Fluid (MS-5931)   |
| Ball Joints, Prop Shafts, U-Joints, Yokes, & Wheel Bearings | Mopar® Multi-Purpose Lube NLGI Grade 2 EP, GC-LB  |