

**2007 JK Wrangler****Engine**

<b>Component</b>	<b>Fluid, Lubricant, or Genuine Part</b>
Engine Coolant	Mopar Antifreeze/Coolant 5 Year/100,000 Mile Formula HOAT (Hybrid Organic Additive Technology)
Engine Oil	API Certified SAE 5W-20 Engine Oil is recommended. Meets the requirements of DaimlerChrysler Material Standard MS-6395
Spark Plugs	Refer to the Vehicle Emission Control Information label in the engine compartment
Oil Filter (3.8L Engine)	Mopar Oil Filter (P/N 04105409AC)
Fuel Selection	87 Octane

**Chassis**

<b>Component</b>	<b>Fluid, Lubricant, or Genuine Part</b>
Automatic Transmission	Mopar ATF+4 Automatic Transmission Fluid
Manual Transmission	Mopar Manual Transmission Lubricant or equivalent (meeting the requirements of DaimlerChrysler Material Standard MS-9224)
Transfer Case	Mopar ATF+4 Automatic Transmission Fluid or equivalent
Axle Differential (Front)	Mopar Gear & Axle Lubricant (SAE 80W-90) (API GL-5) or equivalent
Axle Differential (Rear)	198 RBI (Model 35) and 226 RBI (Model 44) - Mopar Gear & Axle Lubricant (SAE 80W-90) (API GL-5) or equivalent. For trailer towing, use Mopar Synthetic Gear & Axle Lubricant (SAE 75W-140) or equivalent. Models equipped with Trac-Lok require an additive
Brake Master Cylinder	Mopar DOT 3 Brake Fluid, SAE J1703 should be used. If DOT 3, SAE J1703 brake fluid is not available, then DOT 4 is acceptable. Use only recommended brake fluids
Power Steering Reservoir	Mopar ATF+4 Automatic Transmission Fluid